

abit *Engineered*


- | P r e s s C e
- | B I O S G u i
- | C P U s u p p
- | D o w n l o a
- BIOS
- Drivers
- Utilities
- Manuals
- | F A Q s
- | A w a r d s
- | C o n t a c t
- | A b o u t
- R&D
- Customer Service
- Copyright info
- | H O M E
- Newsletter Sign-Up
-
- Subscribe/ Unsubscribe
- Search
-
-
- Product
- FAQs
- News
- Award

MOTHERBOARD Socket 478

Browse by processor

-- Select One -- ▼

BG-72 e



- LGA 478
- Intel® 845GV
- FSB533
- DDR333
- 10/100 LAN
- 5.1 CHAudio

Product Image



Product Information

[Specifications](#)

Support Information

[BIOS](#)

[Driver](#)

[Manual](#)

Specifications

>> CPU

- Intel Pentium 4/ Prescott 533/ Celeron D/ Celeron Socket 478 Processors with 400/ 533 MHz FSB

>> Chipset

- Intel 845GV + ICH4

>> Memory

- Two 184-pin DIMM sockets
- Supports DDR200/ 266/ 333 non-ECC un-buffered memory
- Supports maximum memory capacity up to 2GB

>> Graphic

- Integrated graphics architecture yields higher 2D/3D performance

>> LAN

- On board 10/100M PCI controller

>> Audio

- On board 5.1 channels Audio CODEC

>> Internal I/O Connectors

- 3 x PCI slots
- 1 x Floppy Port supports up to 2.88MB
- 2 x Ultra DMA 100/66/33 Connectors
- 2 x USB 2.0 headers (Each header support two USB 2.0 devices)
- 1 x FP-Audio header, 1 x CD-IN

>> Back Panel I/O

- 1 x PS/2 Keyboard, 1 x PS/2 Mouse
- 1 x Serial Port, 1 x Parallel Port, 1 x VGA connector
- 2 x USB 2.0 + 1 x RJ-45 LAN Connector
- 1 x Audio connectors (Line-out, Line-in, MIC-in)

>> Miscellaneous

- Micro ATX form factor (244mm*200mm)