

abit *Engineered*

- | Press Center
- | BIOS Guide
- | CPU support
- | Downloads
- BIOS
- Drivers
- Utilities
- Manuals
- | FAQs
- | Awards
- | Contact Us
- | About Us
- R&D
- Customer Service
- Copyright info
- | HOME
- Newsletter Sign-Up
-
- Subscribe/ Unsubscribe
- Search
- Product
- FAQs
- News
- Award

MOTHERBOARD LGA775

Browse by processor

-- Select One -- ▾

SG-80e



SIS 661FX Based LGA775 Micro ATX Mainboard
FSB800, Dual DDR400, AGP8X, SATA150
10/100 LAN, 5.1 CH Audio



Product Information

- [Specifications](#)
- [Test Reports](#)

Specifications

- >> CPU**
 - Designed for Intel® 90nm Pentium 4/Celeron D LGA775 Processors with 800/533 MHz FSB
 - Supports Intel Hyper-Threading Technology
- >> Chipset**
 - SIS 661FX/ 964
- >> Memory**
 - Two 184-pin DIMM sockets
 - Supports DDR400 non-ECC un-buffered memory
 - Supports maximum memory capacity up to 2GB
- >> Graphics**
 - Integrated SIS Mirage Graphics GPU high performance 256-bit 3D engine and 2D Accelerator
- >> SATA 150**
 - Serial ATA 1.5Gbps data transfer rate
 - Support SW RAID 0/ 1/ JBOD
- >> Audio**
 - On board 5.1 channels Audio CODEC
- >> LAN**
 - On board 10/100 PHY
- >> Internal I/O Connectors**
 - 1 x AGP 8X/4X slot. 3 x PCI slots
 - 1 x Floppy Port supports up to 2.88MB
 - 2 x Ultra DMA 133/100/66/33 Connectors
 - 2 x Serial ATA 1.5Gbps Connectors
 - 2 x USB 2.0 headers (Each header support two USB 2.0 devices)
 - 1 x FP-Audio header, 1 x CD-IN, 1 x AUX-IN
- >> Back Panel I/O**
 - 1 x PS/2 Keyboard, 1 x PS/2 Mouse
 - 1 x Serial Port, 1 x Parallel Port, 1 x VGA connector
 - 4 x USB 2.0, 1 x RJ-45 LAN Connector
 - 1 x Audio connectors (Line-out, Line-in, MIC-in)
- >> Miscellaneous**
 - Micro ATX form factor (244mm*244mm)

Support Information

- [BIOS](#)
- [Driver](#)
- [Manual](#)