

**Chenbro**  
**RM411xx**  
**www.chenbro.com.tw**



**Product Information**

**Model#:** RM411xx

**Size: (DxWxH in):** 23.5" x 16.6" x 7"

**Size: (DxWxH mm):** 596 x 422 x 177

**5.25" Bays:** 3

**3.50" Bays:** 4 internal, 2 external. Optional HS SCSI bay.

**Cooling:** 1x 120mm Standard, upgradeable

**Power Supply:** 450W single or 460W redundant

**Other Information:** Hot swap fan for SCSI HDD cooling, 3 way key lock

**Note:** The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

**Additional Information**

**Associated Model #s:** RM41111/RM41122/RM41123

**Options:** Up to one additional 80mm and one 60mm fans  
Optional Zippy\* MR3-6460P Redundant Power

**Chassis Configuration** Intel® Server Board SE7501CW2  
Tested Chassis List Based On Mechanical and Thermal  
Regression Testing of Chassis Posted on Server Board  
SE7500CW2 and SHG2 Reference Lists

**Model tested:** RM411XX

**Fans (qty x size):** 1 x 120mm Sunon\* KD1212PTB3-6A, 2x  
60mm Sanyo Denki 109R0612G4031 Processor fans

**Hard drives:** 1 x Seagate\* ST380020A, 1x Western Digital\*  
WD400EB, 1X Western Digital\* WD200BB

**Processor:** Two 2.4Ghz Intel ® Xeon™ processors

**Memory:** 4 X Samsung\* 128M DDR200 DIMM  
M386L1713BT1-CA0

**Power Supply:** NMB GM460WTXW01SSV

**Additional Information:** CD and floppy

\* Third party names and brands are the property of their respective owners.

**Note: Modifications to the tested configuration may cause  
variations in actual performance.**

**List of Intel®**

**Server Boxed Boards**

**Mechanically Compatible with:**

**SHG2, SE7500CW2 & SE7501CW2**

**Thermally Compatible with:**

**SHG2, SE7500CW2 & SE7501CW2**