



2U Rack RS 2100i

www.cidesign.com



Product Information

Model#: RS 1400

Size: (LxWxH in): 26.5 x 19 x 1.75

Size: (LxWxH mm): 673.1 x 482.6 x 44.1

5.25" Bays: slimline CD and FDD

3.50" Bays: 4 x SCA/IDE

Fans: 10 system fans (40mm)

Power Supply: 400W

Other Information: P/S from 300 –480W available

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: Rack Server Series

Options: Fixed IDE, Removable IDE, hot swap SCSI

Chassis Configuration As tested with Intel® Server Board SE7501HG2. Posting on Server Board SE7501BR2 and SE7501CW2 Reference Chassis lists based On Mechanical and Thermal similarity

Model tested: RS 1400

Fans (qty x size): 10 x dual in line NMB* 1611KL-04-B59 fans.

Hard drives: 3 x Seagate* SCSI ST318406LC

Processor: 2 x Intel© 2.8 GHz Xeon™Processors

Memory: 4 x Samsung* 128M DDR266 DIMM M312L1713CTO-CB0

Power Supply: EMACS* 400W P1L-6400P

Additional Information:

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

SE7501BR2, SE7501HG2, SE7501CW2

Thermally Compatible with:

SE7501BR2, SE7501HG2, SE7501CW2

* Third party names and brands are the property of their respective owners.