

**Chenbro**  
**RM411xx**  
**www.chenbro.com.tw**



**Product Information**

**Model#:** RM411xx

**Size: (DxWxH in):** 23.5" x 16.6" x 7"

**Size: (DxWxH mm):** 596 x 422 x 177

**5.25" Bays:** 3

**3.50" Bays:** 4 internal, 2 external. Optional HS SCSI bay.

**Cooling:** 1x 120mm Standard, upgradeable

**Power Supply:** 450W single or 460W redundant

**Other Information:** Hot swap fan for SCSI HDD cooling, 3 way key lock

**Note:** The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

**Additional Information**

**Associated Model #s:** RM41111/RM41122/RM41123

**Options:** Up to one additional 80mm and one 60mm fans  
Optional Zippy\* MR3-6460P Redundant Power

**Chassis Configuration** As tested with Intel® Server Board SE7505VB2.

**Model tested:** RM411XX

**Fans (qty x size):** 1 x 120mm Sunon\* KD1212PTB3-6A, 2x 60mm Nidec Processor fans

**Hard drives:** 3 x Seagate\* ST380021A

**Processor:** 2 x Intel® 3.06GHz Xeon™ Processors

**Memory:** 4 X Samsung\* 128M DDR266 DIMM  
M312L1713CT0-CBA

**Power Supply:** NMB GM460WTXW01SSV

**Additional Information:** CD and floppy

\* Third party names and brands are the property of their respective owners.

**Note:** Modifications to the tested configuration may cause variations in actual performance.

**List of Intel®**

**Server Boxed Boards**

**Mechanically Compatible with:**

**SE7505VB2**

**Thermally Compatible with:**

**SE7505VB2**