

# FEATURES

Compaq ProLiant 2500R

## Compaq ProLiant 2500R 6/200

### System Unit

Microprocessor	200-MHz Intel Pentium® Pro processor
Upgradability	Chip upgradable to dual processing
Cache	512-KB high-speed 4-way set associative cache
Expansion Slots	
I/O (Total)	6
PCI	2
Shared PCI/EISA	4
RAM	
Standard	32 MB
Maximum	1 GB

### Network Interface Controllers

Netelligent 10/100 TXUTP Controller (embedded)	Standard
Netelligent 100 FDDI PCI SAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS Fiber-MIC	Optional
Netelligent 100 FDDI PCI DAS Fiber-SC	Optional
Netelligent 100 FDDI PCI SAS UTP	Optional
Netelligent 100 FDDI PCI DAS UTP	Optional
Netelligent 100 FDDI EISA SAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA DAS Fiber-MIC	Optional
Netelligent 100 FDDI EISA SAS UTP	Optional
Netelligent 100 FDDI EISA DAS UTP	Optional
Netelligent 10 T PCI UTP	Optional
Netelligent 10 T/2 PCI UTP/Coax Controller	Optional
Netelligent 16/4 TR PCI IBM UTP/STP	Optional
Netelligent 4/16 TR PCI UTP/STP	Optional
Netelligent Dual 10/100 TX PCI UTP	Optional
NetFlex-3/P	
100Base-TX UTP Module	Optional (for NetFlex-3)
100VG-AnyLAN UTP Module	Optional (for NetFlex-3)
100Base-FX Module	Optional (for NetFlex-3)

**Compaq ProLiant 2500R 6/200**
**Server Management**

Compaq Insight Manager	Standard
Integrated Remote Console	Standard
Integrated Management Display	Standard
Automatic Server Recovery	Standard
Server Health Logs	Standard
Recovery Server Option	Optional
Compaq Remote Insight Board	Optional

**Storage**

Diskette Drives	1.44-MB
CD-ROM Drives	
Standard	IDE Internal
Optional	IDE or SCSI
Hard Drives <sup>1</sup>	
Standard	—
Optional	2.1-GB, 4.3-GB, 9.1-GB, 18.2-GB Pluggable Wide-Ultra SCSI-3 Drives, 4.3-GB, 9.1-GB Pluggable Wide-Ultra SCSI-3 10,000 rpm Drives
External Storage	
Rack-Mountable ProLiant Storage System Models/F1 and /F2	Optional
Rack-Mountable SCSI Storage Expander	Optional
Maximum Storage Capacity	
Internal	63.7 GB <sup>2</sup>
External	1.15 TB = (7 x 18.2-GB) x 9
CD-Storage System	
Rack Model	Optional
Tape Drives	
Optional	2/4-GB DAT, 4/8-GB SLR, 4/8-GB DAT, 12/24-GB DAT, Internal TurboDAT AutoLoader, Internal 15/30-GB DLT, 35/70-GB DLT, DLT Tape Array, DLT 15 Cartridge Library Model 1530-1, DLT 15 Cartridge Library Models 3570-1 and 3570-2
Controllers	
Standard	Integrated Wide-Ultra SCSI-3
Optional	SMART-2SL Array, SMART-2DH Array, SMART-2/P Array, Wide-Ultra SCSI-3, Dual Channel Wide-Ultra SCSI-3

**Compaq ProLiant 2500R 6/200**
**Interfaces**

Parallel	1
Serial	2
Pointing Device (mouse)	1
Graphics	1
Keyboard	1
External Wide-Ultra SCSI-3	1
Network	
RJ-45	1
AUI	1
BNC	Optional with an AUI BNC converter

**Graphics**

Integrated 1024 x 768 by 256 color noninterlaced Video System	Standard
---	----------

**Monitors**

V55 Color	Optional
V75 Color	Optional
P50 Color	Optional
P75 Color	Optional

**LCD Displays**

Integrated Management Display	Standard
-------------------------------	----------

**Keyboard**

Rack Internal Keyboard	Optional
Rack External Keyboard	Optional

**Supported System Software from Compaq**

Compaq Insight Manager	Standard
Compaq SmartStart	Standard
Microsoft Windows NT Server 3.51	Optional
Novell NetWare 3.20	Optional
Novell intraNetWare	Optional
Computer Associates Products	Optional
SCO UnixWare 2.1	Optional
SCO Open Server Release 3.0	Optional
SCO OpenServer Release 5	Optional
IBM OS/2 v2.1x	Optional
IBM OS/2 Warp 3.0	Optional
IBM LAN Server 3.0x, 4.0	Optional

Compaq ProLiant 2500R 6/200

**Other Supported System Software**

Microsoft BackOffice	Optional
Microsoft Windows NT Server 4.0	Optional
Microsoft Windows NT Workstation 3.51, 4.0	Optional
Novell intraNetWare SFT III	Optional
SCO Open Desktop v3.0	Optional
Banyan VINES v5.5x, 6.0	Optional

<sup>1</sup> Hard drive specifications may vary slightly depending on vendor.

<sup>2</sup> For maximum storage, remove the CD-ROM for an additional 27.3-GB (3 x 9.1-GB drives).