

# Compaq UPS Model Guide

## Compaq Tower UPS Models

Model Number	Part Number	Power Out (VA/Watt)	Input Connection	Output Connections	Dimensions WxHxD	Weight
<b>Low Voltage Models (100–127 VAC; 60 Hz)<sup>1</sup></b>						
T700 <sup>2</sup>	295372-B21	700/420	5-15P	(4) 5-15R	4.6 x 6.4 x 14.8 in 11.68 x 16.26 x 37.6 cm	22 lb/10 kg
T700j <sup>3</sup>	295372-291	700/420	5-15P	(4) 5-15R	4.6 x 6.4 x 14.8 in 11.68 x 16.26 x 37.6 cm	22 lb/10 kg
T1000	242688-001	1000/670	5-15P	(6) 5-15R	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	43 lb/19.5 kg
T1500	242688-003	1440/960	5-15P	(6) 5-15R	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	57 lb/25.85 kg
T1500j <sup>3</sup>	242688-293	1440/960	5-15P	(6) 5-15R	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	57 lb/25.85 kg
T2000	242688-005	1920/1400	5-20P	(8) 5-15R	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	32 lb/14.5 kg
T2000j <sup>3</sup>	242688-295	1920/1400	5-20P	(8) 5-15R	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	32 lb/14.5 kg
<b>High Voltage Models (208–240 VAC; 50/60 Hz)<sup>4</sup></b>						
T700h	295372-B22	700/420	IEC-320 (10 A)	(4) IEC-320 (10 A)	4.6 x 6.4 x 14.8 in 11.68 x 16.26 x 37.6 cm	22 lb/10 kg
T1000h	242688-002	1000/670	IEC-320 (10 A)	(6) IEC-320 (10 A)	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	43 lb/19.5 kg
T1500h	242688-004	1500/960	IEC-320 (10 A)	(6) IEC-320 (10 A)	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	57 lb/25.85 kg
T2400h	242688-006	2300/1600	IEC-320 (10 A)	(9) IEC-320 (10 A)	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	34 lb/15.42 kg
T2400h-NA <sup>5</sup>	242688-007	2300/1600	IEC-320 (10 A)	(9) IEC-320 (10 A)	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	34 lb/15.42 kg
<b>Battery Boxes</b>						
(for T2000)	—	48 VDC, 10 AHr	cord w/connector	—	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	47 lb/21.32 kg
(for T2400h)	—	48 VDC, 17 AHr	cord w/connector	—	7.0 x 8.8 x 17.1 in 17.78 x 22.35 x 44.43 cm	63 lb/28.58 kg

1. User selectable for 100, 110, 120, or 127 VAC. With 100 or 110 VAC selected, unit can operate at 50 Hz.

2. T700 not configurable for 100 VAC.

3. Japanese, 100 volt model.

4. User selectable for 208, 220, 230, or 240 VAC. T700h not configurable for 208 VAC.

5. NA indicates North American high voltage model.

## Compaq Rack-Mount UPS Models

Model Number	Part Number	Power Out (VA/Watt)	Input Connection	Output Connections	Dimensions WxHxD	Weight
<b>Low Voltage Models (100–127 VAC; 60 Hz)<sup>1</sup></b>						
R1500	242704-001	1440/960	5-15P	(6) 5-15R	19.0 x 3.5 x 17.5 in 48.26 x 8.89 x 44.5 cm	58 lb/26.31 kg
R1500j <sup>2</sup>	242704-291	1440/960	5-15P	(6) 5-15R	19.0 x 3.5 x 17.5 in 48.26 x 8.89 x 44.5 cm	58 lb/26.31 kg
R3000	242705-001	2880/2250	L5-30P	(9) 5-15R & (1) L5-30R	19.0 x 5.25 x 22.3 in 48.26 x 13.34 x 56.64 cm	132 lb/59.87 kg
R3000j <sup>2</sup>	242705-291	2880/2250	L6-30P	(9) 5-15R & (1) L6-30R	19.0 x 5.25 x 22.3 in 48.26 x 13.34 x 56.64 cm	132 lb/59.87 kg
<b>High Voltage Models (208–240 VAC; 50/60 Hz)<sup>3</sup></b>						
R1500h	242704-002	1500/960	IEC-320 (10 A)	(6) IEC-320 (10 A)	19.0 x 3.5 x 17.5 in 48.26 x 8.89 x 44.5 cm	58 lb/26.31 kg
R3000h	242705-002	3000/2250	IEC-320 (16 A)	(9) IEC-320 (10 A) & (1) IEC-320 (16 A)	19.0 x 5.25 x 22.3 in 48.26 x 13.34 x 56.64 cm	132 lb/59.87 kg
R3000h-NA <sup>4</sup>	242705-003	3000/2250	IEC-320 (16 A)	(9) IEC-320 (10 A) & (1) IEC-320 (16 A)	19.0 x 5.25 x 22.3 in 48.26 x 13.34 x 56.64 cm	132 lb/59.87 kg

1. User selectable 100, 110, 120, or 127 VAC. With 100 or 110 VAC selected, unit can operate at 50 Hz.

2. Japanese, 100 volt model.

3. User selectable for 208, 220, 230, or 240 VAC.

4. h-NA indicates North American high voltage model.

# Compaq UPS Model Guide *(cont.)*

## Compaq R6000 UPS Models (200-240 VAC;50/60Hz)<sup>1</sup>

Model Number	Part Number	Power Out (VA/Watt)	Input Connection	Output Connections	Dimensions WxHxD	Weight
R6000a <sup>2</sup>	347207-001	6000/6000	Hard-wired	(12) IEC320,10A (3) IEC320,16A	17.25 x 10.5 x 24.3 in. 43.8 x 26.7 x 61.7 cm.	300 lb/136kg
R6000i <sup>3</sup>	347207-B31	6000/6000	Hard-wired	(12) IEC320,10A (3) IEC320,16A	17.25 x 10.5 x 24.3 in. 43.8 x 26.7 x 61.7 cm.	300 lb/136kg
R6000j <sup>4</sup>	347207-291	6000/6000	Hard-wired	(12) IEC320,10A (3) IEC320,16A	17.25 x 10.5 x 24.3 in. 43.8 x 26.7 x 61.7 cm.	300 lb/136kg

1. User selectable for 200, 208, 220, 230, and 240 VAC.

2. a=North American 208 VAC default.

3. i=international 230 VAC default.

4. j=japanese 200 VAC default.

## Compaq R6000 Extended Runtime Module

Part Number	Battery Voltage	Output Connections	Dimensions WxHxD	Weight
347224-B21	360VDC	Custom DC Connector	17.25 x 5.25 x 24.3 in. 43.8 x 13.35 x 61.7 cm.	150 lb/68 kg

1. Designed for use with the Compaq R6000 UPS