

# Silicon Integrated Systems Corp.

# Subject: Release Note for 3.58b VGA Driver Logo

MID for WinXP & Win2K: 819093

### [3.58.b.00]

1. Fix bug -- When display mode is "CRT only" and didn't connect CRT to notebook, it can't switch to LCD

## [3.58a.00]

1. Fix bug -- LCD change mode to 800\*600, restart windows will change to the maximum resolution

### [3.58.51]

- 1. Fix bug -- LCD panel cannot set to the Max resultion if using INF install.
- 2. Fix bug -- XP Mirror mode(TV+CRT) TV 800\*600 and 1024\*768 display is incorrect
- 3. Fix bug -- DCTDX9 QFE dual view test "Ratetest" will fail.
- 4. Add new feature for customer could change the driver path name from setup.ini.
- 5. Fix bug -- PAL-M Macrovision is not correct issue.

#### [3.58.50]

- 1. Fix bug -- Can't change display when press Hotkey under Full screen DOS
- 2. Fix bug Fail to change to LCD+TV mirror mode by hot key when only connect the TV

#### [3.58.50]

- Fix bug There is error message and resolution become 640x480x4bpp when running PCMark04 on 760 UMA 64MB
- 2. Fix bug -- After using INF update method to install driver, screen resolution is 640x480 and Color quality is low (8 bit).
- 3. Unify the installation between WinNT and Win9x.

## [3.58.02]

1. Fix bug -- CRT Single Virtual screen mode, it's unable to change "Overfly" size.

#### [3.58.00]

1. Fix bug -- When AP "O verfly" is running on CRT2 with full screen size, "Overfly" on CRT1 displays abnormally after changing its size to full screen size.



# Silicon Integrated Systems Corp.

- 2. Fix bug -- Screen blinks on Strech-eye Hyper LE
- 3. Fix bug -- HCT 11.2 fail
- 4. Add mode support for 1280x720, 1280x768, 1280x800 and 1680x1050.

# [3.58.00]

- 1. Fix bug -- CRT1 becomes black when overlay is shown on CRT2 and the size is equal to the display resolution size.
- 2. Add mode support for 1280x720, 1280x768, 1280x800 and 1680x1050.