



Elan Vital S-30T

www.elanvital.com.tw

Additional Information

Associated Model #s: S-30RM

Options: 1 or 2 SCA modules, rack kit

Chassis Configuration (as tested with Intel's L440GX+ Server Board)

Model tested: S-30T

Fans (qty/size): 2 x 80 mm, 2 x 60 mm (in SCA module)

Hard drives: 3 x Seagate* ST39102LC Cheetah*

Processor: 2 x 850Mhz Pentium® III

Memory: 512 MB

Power Supply: Elan Vital EVB-3006A

RAID: Intel, BOXSRCU21

Additional Information: Tested with 1 SCA 1" module

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850 MHz)

Thermally Compatible with:

L440GX+ (850 MHz)

CE Testing Performed with:

Product Information

Model#: S-30T

Size (LxWxH in/mm): 23.8 x 17.2 x 8.7"/605 X 437 x 220mm

5.25" Bays: 8 configurable as described below

3.50" Bays: 1-3.5" floppy carrier with 7 - 5.25" bays

1-3.5" floppy carrier with 2 SCA modules (10-1" HDD)

1-3.5" floppy carrier with 3-5.25" bays and

1 SCA module (5-1" HDD)

Fans: 2 x 80 mm (2 x 60 mm in each SCA module)

Power Supply: Elan Vital EVB-3006/ 300 W

Other Information: Flexible configuration-Hot swap SCA module, Removable SCA fan module for easy maintenance, 1" or 1.6" SCA backplane, Tower and rack convertible

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.