



Siliconrax SR-4268 ATX

www.siliconrax.com

Product Information

Model#: SR-4268ATX

Size (LxWxH in/mm): 19 x 26 x 7"/483 X 660 x 178mm

5.25" Bays: 8

3.50" Bays: 9

Fans: 3 Hot Swap 105 CFM In-take fans

Power Supply: Orion 600NRX or Top Micro P6400 (400W)

Other Information: Removable Air Filter, Lockable Dust proof Disk Drive Door, Keyboard connector on Both front and rear panels

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s: SR-4268L, SR-4268R

Options: Hot swap drives

Redundant Power Supply

Chassis Configuration (as tested with Intel's L440GX+ server board)

Model tested: SR-4268ATX

Fans (size, qty): 3-120 mm

Hard drives: 3-Seagate* ST39102LC Cheetah*

Processor: 2 x 450MHz Pentium® II

Memory: 512 MB

Power Supply: Sparkle* FSP300-60GT

Additional Information: Power supply tested is not standard or currently roadmap. Configuration of hard drives were loaded in the center of the hot swap bay.

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanical Validation

L440GX+

Thermal Validation

L440GX+

EMI (CISPR) Validation