



Siliconrax Sliger

www.siliconrax-sliger.com

Product Information

Model# SR-CX479H-ATX

Size (LxWxH inches/mm) 26 x 19 x 7 / 660 x 483 x 178

5.25" Bays: 7

3.50" Bays (internal/external): 1/0

Fans: 3 x 10.5cm

Power Supply : Sparkle Power FSP400-60GN

Other Information: Optional Hot Swap Drive Bay, 300 Watt Redundant Power Supply option, Shock mounted drive bays, add-in card retention,

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Additional Information

Associated Model #s:

Options: Hot swap drives, redundant power supply selection

Chassis Configuration (as tested with Intel's L440GX+ Server Board)

Model tested: SR-CX479H-ATX

Fans: 3 x 105mm

Hard drives: 3 x Seagate* ST39102LC Cheetah*

Processor: 2 x 850MHz Pentium® III

Memory: 512 MB

Power Supply: Sparkle Power FSP400-60GN

RAID: Intel, BOXSRCU21

Additional Information:

* Third Party names and brands are the property of the respective owner.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanically Compatible with:

L440GX+ (850 MHz)

Thermally Compatible with:

L440GX+ (850 MHz)

CE Testing Performed with: