



Fong Kai, USA FK-600ATX

www.fkusa.com

Product Information

Model#: FK-600ATX

Size (LxWxH in/mm): 19.1x8.66x17.33in/485x220x440mm

5.25" Bays: 3

3.50" Bays: 3

Fans: 2 x 8cm (1 x 8 cm optional)

Power Supply: Bestec 250W/SPI 300W

Other Information: Fan duct cooling system available, screw-less side access, screw-less drive access. Main board Specs: AT, ATX, ATXII, Thickness: 1.0mm, Hardness: over 3H, Material: SECC Galvanized Sheet Iron, Expansion Slots: 7

Note: The above information is provided by the chassis manufacturer and is the sole responsibility of the manufacturer. Intel assumes no responsibility for any inaccuracies in this data or any changes made by the manufacturer.

Chassis Configuration (as tested with Intel's L440GX+ server board)

Model tested: FK-600ATX

Fans (qty x size): 2 x 8 cm

Hard drives: 3 - Seagate* ST39102LW Cheetah*

Processor: 2 - 450Mhz Pentium® II processor

Memory: 512MB SDRAM

Power Supply: Sparkle* FSP-300-60GT

Additional Information: Thermal testing conducted by Northwest EMC, Inc. under Intel guidelines.

* Third party names and brands are the property of their respective owners.

Note: Modifications to the tested configuration may cause variations in actual performance.

List of Intel

Real Server Boxed Boards

Mechanical Validation

L440GX+

Thermal Validation

L440GX+

EMI (CISPR) Validation