
The Atmel 3-Volt EPROM Family

- Why 3-volt operation?
- Does the whole system have to be operated at 3 volts?
- How do you program a 3-volt EPROM?
- What happens if you run a 3-volt device at 3.6 volts?

The Atmel AT27LVxxxA series of EPROMs was designed to operate over a wide range of supply voltages from 3.0 to 3.6 volts. This offers the designer the opportunity to take advantage of the greatly reduced power consumption at 3 volts.

The 3-volt series of EPROMs is specified to draw a maximum of 8.0 mA at 5.0 MHz when operated at 3.6VDC. This is less than half of the specified maximum current of a standard EPROM operating at 5.0VDC. Because of the low supply voltage, the power savings calculations are even more dramatic: 29 mW for the LV series compared to 165 mW (5.5V @ 30 mA; i.e. 27C040) for standard five-volt devices. That means much longer battery life.

The LV series has CMOS inputs and outputs specified for TTL levels and 3-volt CMOS levels (Rail-to-Rail). In other words, an LV device with $V_{CC} = 3.0\text{VDC}$ can drive standard 5-volt TTL logic devices on its data output lines making interface with 5-volt logic easy. The LV series of EPROMs can even be safely driven by 5-volt signals, even though

their V_{CC} is at 3.0VDC (please refer to application note *Interfacing Atmel LV EPROMs on a Mixed Three-Volt/Five-Volt Data Bus*, this chapter). The next question that comes to mind is "Why run just one EPROM at 3 volts while the rest of the system uses 5 volts?" One reason is if your system is on a very tight power budget, such as battery operated equipment, daughter boards or phone line powered products, the **six times** power savings might make a significant difference. Of course your design might use more than one EPROM, for map memory, operating system, font storage or maybe smart cards. In this case the total power savings can be very large. Remember at 165 mW each, 8 EPROMs at 5 volts use 1.3 Watts instead of 235 mW for the 3-volt devices!

When the 3-volt devices are in a programmer they work just like their standard Atmel 5-volt counterparts. Absolutely no difference! Programming support is already in place and widely available on most programmers on the market today.

The AT27LVxxxA series of EPROMs are specified to operate from 3.0 to 3.6 volts. So what happens when the device is operated above 3 volts? It speeds up and draws more power, but never more than a standard EPROM. This feature offers the most flexibility for system manufacturers.



Low Voltage OTP EPROM







Atmel Headquarters

Corporate Headquarters
2325 Orchard Parkway
San Jose, CA 95131
TEL (408) 441-0311
FAX (408) 487-2600

Europe

Atmel U.K., Ltd.
Coliseum Business Centre
Riverside Way
Camberley, Surrey GU15 3YL
England
TEL (44) 1276-686677
FAX (44) 1276-686697

Asia

Atmel Asia, Ltd.
Room 1219
Chinachem Golden Plaza
77 Mody Road
Tsimshatsui East
Kowloon, Hong Kong
TEL (852) 27219778
FAX (852) 27221369

Japan

Atmel Japan K.K.
Tonetsu Shinkawa Bldg., 9F
1-24-8 Shinkawa
Chuo-ku, Tokyo 104-0033
Japan
TEL (81) 3-3523-3551
FAX (81) 3-3523-7581

Atmel Operations

Atmel Colorado Springs
1150 E. Cheyenne Mtn. Blvd.
Colorado Springs, CO 80906
TEL (719) 576-3300
FAX (719) 540-1759

Atmel Rousset

Zone Industrielle
13106 Rousset Cedex, France
TEL (33) 4 42 53 60 00
FAX (33) 4 42 53 60 01

Fax-on-Demand

North America:
1-(800) 292-8635
International:
1-(408) 441-0732

e-mail

literature@atmel.com

Web Site

<http://www.atmel.com>

BBS

1-(408) 436-4309

© Atmel Corporation 1998.

Atmel Corporation makes no warranty for the use of its products, other than those expressly contained in the Company's standard warranty which is detailed in Atmel's Terms and Conditions located on the Company's website. The Company assumes no responsibility for any errors which may appear in this document, reserves the right to change devices or specifications detailed herein at any time without notice, and does not make any commitment to update the information contained herein. No licenses to patents or other intellectual property of Atmel are granted by the Company in connection with the sale of Atmel products, expressly or by implication. Atmel's products are not authorized for use as critical components in life support devices or systems.

Marks bearing ® and/or ™ are registered trademarks and trademarks of Atmel Corporation.

Terms and product names in this document may be trademarks of others.



Printed on recycled paper.

0546A-10/98/xM